

DOVE

technical sheet



This product consists of 2 main modules.

- Product: Bergere
- Product: Pouf

STRUCTURE

The main frame carrier parts are 1.8 cm beech plywood. Supporting pillars are 1.8 cm poplar plywood. The seating is reinforced with a 3 mm thick felt pad. Springs have a decisive influence on seating comfort. Specific to the Dove, Caridia utilizes elastic gimped webbing in order to offer a comfortable feeling without compromising quality.

SEATING COMFORT

The seating and backrest are monobloc and designed as High Resilient (HR) foam. Caridia aims balancing the rigidity and the comfortability of DOVE by employing a unique foam design in order to emphasize the quality sitting and perfect appearance. The sitting cushion is composed of three layers of foam at different density levels, 35 HR at the bottom and 25 HR in the middle, and 25 memory foam on top of it, and finally coated with 250 g/m² fiberfill wrap. The inner back is coated with 25 HR and 50 DNS Visco memory foam as two layers and wrapped with 250 g/m² fiberfill wrap. Rest outer parts of the bergère is coated with 25 HR foam to underline the visuality and feeling, and wrapped with 250 g/m² fiberfill wrap.

LEGS

While DOVE stands out with its custom design wood leg design, it is also offered with metal swivel base.

STRUCTURE

FRAME	Plywood + Beech Plywood + MDF
SPRINGS	Elastic Gimped Webbing
LEGS	Custom Design Wood Legs or Metal Swivel Base
SEATING	35 HR + 25 HR + 25 Memory Foam + Fiber 250 g/m ²
BACKREST	25 HR + 50 DNS Visco Memory Foam + Fiber 250 g/m ²
FRAME	25 DNS Foam + Fiber 250 g/m ²
FABRIC USAGE	Bergere - 3,8 m
	Pouf - 1 m
m ³ (paketlenmiş)	Bergere: 0,54 m ³
	Pouf : 0,11 m ³